VISION

BLUE





Blue Vision



Vision Perfect Cooking

Page 6

Vision Design

Page 8

My Vision Controls

Page 10

Smart Investment

Page 12

VISION PERFECT COOKING

I can be absolutely certain that my cooking results will always be of outstanding quality. The foods that I prepare have perfect colour, are juicy, crispy and healthy, with a minimum amount of fat.



Outstanding steam cooking results

The advanced Retigo Vision steam generation system ensures great colour, taste and consistency of prepared meals, while retaining the maximum amount of vitamins and nutrients.

Ideal colour and crispiness of meals

The Active Humidity Control (AHC) is a precision humidity control system that maintains the ideal climate for the prepared meals. Thanks to unique technology, the cooking chamber may be quickly and effectively dehumidified if necessary. The result is food with perfect crispiness and golden brown colour.



The option to cook multiple meals simultaneously in the same mode with varying cooking times, and without smell or flavour cross-contamination helps to increase the kitchen's capacity. Utilising functions such as Overnight cooking or Low-temperature baking gives the chef more time during the morning rush-hours and achieves greater utilisation of the prepared meals. All of this under HACCP control.

All cooking technologies contained in a single appliance

The Retigo Vision is a single cooking system for the majority of cooking methods (cooking, boiling, baking, stewing, frying, grilling, toasting, confit, cooking under vacuum – Sous-Vide, canning, dehydrating, blanching, leavening, smoking, curing, low temperature procedures, keeping warm and meal regeneration).







Comfortable cooking without the risk of injury

Crosswise racks ensure the safe handling of gastronorm containers and provide a perfect view of the cooking process in the individual racks. Smaller gastronorm containers in a single drawer simply side by side on stainless racks or dedicated adapters.

Minimal risk of burns

The unique triple-glazed door glass solution* reduces its surface temperature and eliminates the risk of burns. The automatic fan stop prevents the dangerous release of steam when the combi oven door is opened, and coupled with a double opening door** ensures maximum safety.

Easy combi oven opening

Ergonomic handle shape makes sure that the combi oven door is easy to handle and the maintenance is easy. By using silver ions, significant reduction of the amount of bacteria present on the handle surface was achieved and as a result, hygienic risks were minimised.

Guaranteed to meet hygiene standards

Precise workmanship inside the cooking chamber with curved edges increases the efficiency of the automatic cleaning and prevents the accumulation of dirt. The HACCP system automatically records everything that happens inside the Retigo Vision combi oven, stored data can subsequently be shown on the display or downloaded on to a PC.







Absolute focus on cooking

Easy control without a manual, perfect overview at all times thanks to the large, colour display.

No more unpleasant delays

Instant response of the 8" screen when pressed and quick selection of frequently used recipes directly on the main screen.

Everything you need is located on the main screen

Option to add any menu function on the main screen and adjust its position, size and colour based on the needs of each chef.

100% time usage

No need to wait for the combi oven to finish its work. While a common cooking process is running, Multitasking allows you to navigate through the combi oven menu in background and work on the display whilst the combi oven continues cooking.

Customising the main menu

Every chef can customise his/her main menu exactly as needed. Thanks to the Profiles function, virtually any number of profile presets can be saved for even more chefs in a single operation.









Two-stage water preheater utilises heat from waste steam and, in combination with the unique triple-glazed door glass solution* and 2 in thick thermal insulation, reduces cooking costs to a minimum.

Economical cleaning

The unique automatic Retigo Active Cleaning system ensures perfect cleanliness of the Retigo Vision combi oven while minimising water consumption and saving money on detergents.

Unbeatable return on investment

Low operating costs, long lifetime, affordable service and repairs, and an outstanding price-to-quality ratio delivers great return on investment.

Kitchen space savings

Retigo Vision can substitute even several classic kitchen appliances with much less space. In addition, with a provably higher yield and raw material processing efficiency.





* Not applicable to 623 size

SMART INVESTMENT

A comparison of new and previous Retigo Vision

Retigo Vision combi ovens have always rated among the top in the water and energy consumption economy. Innovative new generation solutions cut the values down even more, thus the new Vision is rated among the most saving combi ovens in the market.

	Previous generation	New generation	Savings
Preheating in the Hot air mode to 329 °F	3:39 min	3:12 min	12% faster temperature build-up
Energy consumption in Hot air mode with load	2.46 kWh	2.17 kWh	12% lower consumption
Energy consumption in Hot air mode without load (sensible heat)	0.95 kWh	0.66 kWh	31% lower thermal losses

Measured on 611 size combi oven pursuant to DIN 18873-1 2012-6 6.2.

An example of savings with Retigo automatic cleaning

Highly efficient cleaning programs will provide perfect cleanliness with minimum effort. Excellent detergent price, low water and energy consumption will save everyday costs.

Retigo 1011 combi oven in comparison to other high class combi oven brand 1011 model. 6 cleanings per week, 52 working weeks in year. Valid manufacturers' price lists 05/2017 used. Medium cleaning done based on the number of detergents repeteadly required by both machines.

	1 year savings	10 year savings	Benefit
Detergent cost savings	\$225	\$2,246	More than 20% of the combi oven price paid back
Time savings	338 h	3 380 h	Up to you how to use this time savings
Water savings	1,986 gal	19,864 gal	Significant money and environment savings
Energy savings	580 kWh	5,803 kWh	Check your energy prices, you will wonder about money savings

An example of savings with Retigo Vision

In comparison with conventional kitchen appliances.

The Multifunction Retigo Vision cooking system can substitute several conventional kitchen appliances to an area less than 10.8 ft².

Pork	Conventional oven cooking	Retigo Vision	
Yield	64%	80%	
Number of portions (0.22 lb per portion)	100	100	
Amount of raw meat	22 lb	22 lb	
Total yield	14.1 lb	17.6 lb	
Number of days	200	200	
Meat weight loss	1,587 lb	882 lb	
Loss of money	\$7,332	\$4,075	
Total savings in 200 days		\$3,257	

Calculated with an average price of \$4.62 per 1 lb of pork. Comparison with B611i type combi oven.

Cooking of vegetables (potatoes)	Classic cooking	Retigo Vision
Yield	90%	100%
Number of portions (0.22 lb per portion)	100	100
Amount of vegetables	44 lb	44 lb
Cooking time	1.5 h	1 h
Total yield	39.7 lb	44 lb
Number of days	200	200
Vegetables weight loss	882 lb	0 lb
Loss of money	\$833.5	\$0
Total savings in 200 days		\$833

Calculated with an average price of \$0.945 per 1 lb of potatoes. Comparison with B611i type combi oven.

Cooking water and energy consumption	21 gal boiler	Retigo Vision	
Water consumption per hour	10.6 gal	3.2 gal	
Maximum equipment capacity	132 lb	119 lb	
Energy consumption per hour	12 kW	4.5 kW	
Cooking time	1.5 h	1 h	
Total consumption for 1 cooking	18 kWh	4.5 kWh	
Total costs of 1 cooking	\$2.99	\$0.75	
Total savings in 200 days		\$448	
Water saving in 200 days		1,480 gal	

Calculated with an average price of \$0.166 per 1 kW. Comparison with B611i type combi oven.

14 15







Easy Cooking

An intelligent cooking assistant that helps even somewhat less experienced cooks achieve great results. The unique system automatically proposes the correct procedure for each type of meal.



Sous-vide

Utilising the latest technologies, the Retigo Vision can provide the ideal climate, temperature and time for cooking meals sous-vide. Compared to a classic sous-vide water bath, it provides immeasurably greater capacity and quality.



Smoking

Thanks to the Retigo Smoker external smoke generator and special recipes, the Retigo Vision becomes a complete smoker capable of smoking a wide range of meals from a la carte meals to standard whole meats, e.g. hams, shanks.



Overnight cooking

Retigo Vision cooks for you overnight. The special overnight cooking function can, thanks to precise humidity regulation and temperature control, ensure a high yield. Meat will be wonderfully juicy while water and power consumption are kept to a minimum.



Rack timing

System for short order cooking, which monitors food cooking time at each individual Retigo Vision rack. It enables combining several meals at once irrespective of their size or their required cooking time. When the rack timing function is started, the system will automatically offer the cook further recipes that can be prepared at the same time.



Confit

For preparing meals in fat or in their own juices, it is necessary to have two-way airflow, which Retigo Vision achieves by means of a unique fan that can be set to the ideal speed. The confit process requires no supervision and the results are always perfect.



RETIGO GREEN CONCEPT

A combination of unique technical solutions, which will save the user money, while at the same time helping to save the environment.



Minimisation of thermal losses

The special insulation of the cooking chamber and the triple-glazed door glass* on the Retigo Vision ensure the lowest possible power consumption during the cooking process.



Water saving system

A unique waste water system design that requires a negligible amount of water for cooling the exhaust steam. This solution significantly reduces total water consumption.



Advanced steam generation system

Ensures fast generation of highly saturated steam by means of an integrated heat exchanger with minimal demands on water and power consumption.



The lifetime of the combi oven does not end with its disposal

Up to 98% of the materials used in the manufacture of the Retigo Vision are fully recyclable.

UNIQUE TECHNICAL DETAILS



Special surface treatment on the cooking chamber by means of passivation significantly increases its resistance against undesirable substances contained in water or food and prevents the accumulation of dirt.



Quality austenite (non-magnetic) stainless steel (AISI 304 and 316) and the minimal use of plastic components greatly extends the lifetime of the Retigo Vision.



All boiler-type Retigo Vision combi ovens are also equipped with a advanced direct injection system that ensures problem-free operation of the combi oven in the event of an unexpected boiler outage.



The unique fan solution ensures high air replacement efficiency in the cooking chamber to achieve perfect crispiness of the cooked meals.



The automatic humidity control system (AHC) precisely regulates the amount of steam in the cooking chamber and creates the ideal climate for the meals that are being prepared.



A highly powerful flap will provide an immediate discharge of residual moisture from the cooking chamber. This will result in a perfect crispness and accurate colour of foods.

* Not applicable to 623 size

UNIQUE FEATURES



Vision perfect cooking

With Retigo Vision combi ovens, you have the peace of mind that you will always achieve outstanding cooking results. The prepared foods have a perfect colour, are juicy, crispy and healthy and cooked using a minimal amount of fat.

- Excellent steam cooking results
- Ideal food colour and crunchiness
- Less stress in the kitchen
- All technological tasks in a single unit



My Vision Controls

The simpliest controls on the market will save you time and enable you to quickly and easily make all the necessary settings. Display response is perfect even when your hands are greasy or when you are wearing gloves. You can adapt the main menu to your needs.

- Total concentration on cooking
- No wasted time
- Everything necessary is found on the main screen



Vision Design

The Retigo Vision combi oven offers you an excellent combination of features, exceptional ergonomics and attractive appearance. All this with a focus on safety and hygiene.

- Comfortable cooking with no risk of suffering burns
- High reliability and long service life
- Guaranteed to meet public health standards
- High reliability



Smart investment

With the Retigo Vision combi oven, you are saving money every day. Demonstrably lower power and water consumption combined with low cost automatic cleaning, will ensure a fast return on investment.

- Energy savings
- Economical automatic cleaning
- Unparalleled return on investment

STANDARD FEATURES AND UNIT OPTIONS

COOKING

Hot air 86-572 °F

Combination 86-572 °F

Steaming 86-266 °F

Proofing 86-208 °F

Over night cooking - Saves time and money.

Rack timing – Set individual rack times for multi product cooking.

AHC (Active Humidity Control) – Automatic humidity control

for great cooking results.

Advanced steam generation system – Two-step water preheating with built-in heat exchanger for perfect steam cooking results.

Crosswise racks – Safer and comfortable pans handling. Better product visual control.

Regeneration/banqueting – Cook, chill and regenerate to serve more diners in shorther times.

Delta T cooking – Use advanced cooking method to reduce shrinkage on slow roasted meats getting amazing results.

Low temperature cooking – Benefit from less weight loss, better taste.

Cook & Hold – Let it cook and held serving temperature.

Golden Touch – Add a golden-brown, crispy finish with just a touch.

Automatic preheating/cooling minimises the loading temperature drop. Start cooking with the desired temperature.

Sous-vide, Drying, Sterilization, Confit, Smoking – Great way to make your menu special.

MY VISION CONTROLS

8" display – Perfect overview, easy and intuitive control.

MyVision – Customize your menu so you have all you need right on the main screen.

Touch panel – Panel works under all conditions and has a fast response, no mechanical elements, buttons or wheels.

Easy Cooking – Get great results even with less experienced chefs thanks to easy cooking guidance.

6-point core probe – Allows foods to be automatically cooked to any desired internal temperature.

1000 programs with 20 steps

Pictograms – Take a food picture on the main screen. Match it with a program. Touch it to get the desired cooking results repeatedly.

Learn function – All cooking adjustments are recorded. At the end you save great results achieved and recall them again when needed.

Last 10 – Cooking process easy to be used again by just a touch.

Multitasking – Unique opportunity to work with a display during cooking.

Automatic start – The ability to schedule a delayed start.

EcoLogic – Energy consumption shown right on the screen.

Keeps your cost under control.

Continuous cooking time option – Saves your time during busy operations.

OTHER EQUIPMENT

Active Cleaning – Low-cost automatic cleaning. No chef's time spent on cleaning any more.

Triple pane glass door*** – Advanced energy savings and external glass that does not burn you.

Auto-reversing fan – Excellent evenness to deliver high product color and texture uniformity.

Flap valve – Patented dehumidification system for great colour and crispiness

7 Fan speeds*** – Precise control of air distribution for desired results with different products.

Automatic Fan stop*** – No scalding when the door

Fan timing*** – 3 steps for greater evenness and gentle cooking.

Massive door handle – Comfortable and safe handling with silver ion material contain for bacteria reduction.

AISI 304 and 316 stainless steel – Exceptional quality with a special coating for an extended life time.

Hygienic cooking chamber with round inner corners – Trouble free maintenance.

Hand shower – External water supply hose with spray nozzle. Extra water source at your disposal.

Run-off tray under the door – No slipping on wet floor.

Two water inlets – Saves a water treatment unit's capacity.

WSS (Water Saving System) – Special drain system & built-in heat exchanger to save water related cost.

CONECTIVITY

USB plug-in – Transfer useful data easily to and from the combi oven.

Ethernet/LAN – Allows remote access for data management.

VisionCombi software – Program and pictogram management in your PC, HACCP data view.

OPERATION LOGS

HACCP records – Easy and immediate analysis of critical cooking points.

Complete operating records

SERVICE

BCS* (Boiler Control System) – Nothing stops you steam cooking with the in-built advance direct steam generation system.

SDS (Service Diagnostic System) – Easy unit check up and trouble shooting.

UNIT OPTIONS

Left door**

Safety door opening in two steps

Accessories – stands, trolleys, cleaning agents etc.



FULL SIZE MODELS AND TECHNICAL DETAILS

Suitable solution for each facility.







B 1021

Model	B 621i	B 621ig	B 1021i	B 1021ig	B 1221i
Energy	electricity	gas*	electricity	gas*	electricity
Steam generator	boilerless	boilerless	boilerless	boilerless	boilerless
Capacity (sheet pan)	14 x 1/2 sheet pans 7 x full sheet pans	14 x 1/2 sheet pans 7 x full sheet pans	22 x 1/2 sheet pans 11 x full sheet pans	22 x 1/2 sheet pans 11 x full sheet pans	24 x 1/2 sheet pans 12 x full sheet pans
Capacity (hotel pan)	14 x full size hotel pans	14 x full size hotel pans	22 x full size hotel pans	22 x full size hotel pans	24 x full size hotel pans
Capacity of meals	100-300	100-300	300-500	300-500	400-600
Spacing	2.9"	2.9"	2.9"	2.9"	2.6"
Dimensions (w×h×d) [in]	44.1" × 32.6" × 40.1"	44.1" × 32.6" × 40.1"	44.1" × 42.8" × 40.1"	44.1" × 42.8" × 40.1"	43.7" × 52.9" × 37.8"
Weight	333 lb	353 lb	425.5 lb	447.5 lb	463 lb
Heat power	14.7 kW	99,000 BTU/hr	23.7 kW	135,000 BTU/hr	29.4 kW
Total power	15.3 kW	0.8 kW	24.3 kW	0.9 kW	30.3 kW
Steam generation power	-	-	-	-	-
Fuse	45 A	15 A	70 A	15 A	90 A
Voltage	208V/60Hz/3Ph	120V/60Hz/1Ph	208V/60Hz/3Ph	120V/60Hz/1Ph	208V/60Hz/3Ph
Water/Drain connection [in]	G 3/4" / 2" OD	G 3/4" / 2" OD	G 3/4" / 2" OD	G 3/4" / 2" OD	G 3/4" / 2" OD
Gas connection	-	NPT 3/4"	-	NPT 3/4"	-
Noise level	max. 70 dBA	max. 70 dBA	max. 70 dBA	max. 70 dBA	max. 70 dBA
Temperature	86-572 °F	86-572 °F	86-572 °F	86-572 °F	86-572 °F



























B 2021

B 1221b	B 1221ig	B 2021i	B 2021b	B 2021ig
electricity	gas*	electricity	electricity	gas*
boiler	boilerless	boilerless	boiler	boilerless
24 x 1/2 sheet pans 12 x full sheet pans	24 x 1/2 sheet pans 12 x full sheet pans	40 x 1/2 sheet pans 20 x full sheet pans	40 x 1/2 sheet pans 20 x full sheet pans	40 x 1/2 sheet pans 20 x full sheet pans
24 x full size hotel pans	24 x full size hotel pans	40 x full size hotel pans	40 x full size hotel pans	40 x full size hotel pans
400-600	400-600	600-900	600-900	600-900
2.6"	2.6"	2.5"	2.5"	2.5"
43.7" × 52.9" × 37.8"	43.7" × 52.9" × 37.8"	45.5" × 71.4" × 37.9"	45.5" × 71.4" × 37.9"	45.5" × 71.4" × 37.9"
485 lb	504 lb	728 lb	740 lb	834 lb
29.4 kW	160,000 BTU/hr	47.4 kW	47.4 kW	280,000 BTU/hr
30.3 kW	1.4 kW	48.3 kW	48.3 kW	1.6 kW
27 kW	-	-	39.3 kW	-
90 A	20 A	150 A	150 A	20 A
208V/60Hz/3Ph	120V/60Hz/1Ph	208V/60Hz/3Ph	208V/60Hz/3Ph	120V/60Hz/1Ph
G 3/4" / 2" OD				
-	NPT 3/4"	-	-	NPT 1"
max. 70 dBA				
86-572°F	86-572 °F	86-572 °F	86-572 °F	86-572 °F

i – boilerless | b – boiler | g – gas

HALF SIZE MODELS AND TECHNICAL DETAILS

Suitable solution for each facility.





B 623 B 611

Model	B 623i	B 611i	B 611b	B 611ig
Energy	electricity	electricity	electricity	gas*
Steam generator	boilerless	boilerless	boiler	boilerless
Capacity (sheet pan)	6 x 1/2 sheet pans	7 x 1/2 sheet pans	7 x 1/2 sheet pans	7 x 1/2 sheet pans
Capacity (hotel pan)	6 x 1/2 hotel pans	7 x full size hotel pans	7 x full size hotel pans	7 x full size hotel pans
Capacity of meals	30-50	51–150	51–150	51–150
Spacing	2.6"	2.6"	2.6"	2.6"
Dimensions (w×h×d) [in]	26.9" × 23.7" × 23.1"	36.7" × 32.6" × 32.3"	36.7" × 32.6" × 32.3"	36.7" × 32.6" × 32.3"
Weight	136 lb	255 lb	268 lb	280 lb
Heat power	3.9 kW	8.4 kW	8.4 kW	46,000 BTU/hr
Total power	4.2 kW	9 kW	9 kW	0.8 kW
Steam generation power	-	-	7.4 kW	-
Fuse	15 A	30 A	30 A	10 A
Voltage	208V/60Hz/3Ph	208V/60Hz/3Ph	208V/60Hz/3Ph	120V/60Hz/1Ph
Water/Drain connection [in]	G 3/4" / 1.6" OD	G 3/4" / 2" OD	G 3/4" / 2" OD	G 3/4" / 2" OD
Gas connection	-	-	-	NPT 3/4"
Noise level	max. 70 dBA	max. 70 dBA	max. 70 dBA	max. 70 dBA
Temperature	86-572°F	86-572 °F	86-572 °F	86-572 °F





B 1011

B 2011

B 1011i	B 1011b	B 1011ig	B 2011i	B 2011b	B 2011ig
electricity	electricity	gas*	electricity	electricity	gas*
boilerless	boiler	boilerless	boilerless	boiler	boilerless
11 x 1/2 sheet pans	11 x 1/2 sheet pans	11 x 1/2 sheet pans	20 x 1/2 sheet pans	20 x 1/2 sheet pans	20 x 1/2 sheet pans
11 x full size hotel pans	11 x full size hotel pans	11 x full size hotel pans	20 x full size hotel pans	20 x full size hotel pans	20 x full size hotel
151-250	151-250	151–250	400-600	400-600	400-600
2.6"	2.6"	2.6"	2.5"	2.5"	2.5"
36.7" × 42.8" × 32.3"	36.7" × 42.8" × 32.3"	36.7" × 42.8" × 32.3"	37.3" × 71" × 32.8"	37.3" × 71" × 32.8"	37.3" × 71" × 32.8°
304 lb	316 lb	328 lb	518 lb	540 lb	566 lb
14.7 kW	14.7 kW	80,000 BTU/hr	29.4 kW	29.4 kW	160,000 BTU/hr
15.3 kW	15.3 kW	0.8 kW	30.3 kW	30.3 kW	1.4 kW
-	14.7 kW	-	-	27 kW	-
45 A	45 A	15 A	90 A	90 A	20 A
208V/60Hz/3Ph	208V/60Hz/3Ph	120V/60Hz/1Ph	208V/60Hz/3Ph	208V/60Hz/3Ph	120V/60Hz/1Ph
G 3/4" / 2" OD	G 3/4" / 2" OD				
-	-	NPT 3/4"	-	-	NPT 3/4"
max. 70 dBA	max. 70 dBA				
86-572 °F	86-572 °F	86-572°F	86-572 °F	86-572 °F	86-572 °F

Certified by



















SETS AND ACCESSORY OPTIONS



RETIGO VISION COMBI OVEN + STAND

FULL SIZE MODELS

Two stands are available for the installation of combi ovens 621 and 1021 in a kitchen – standard with 7 Half size & 7 Full size racks (ST621/1021) or folding stand with 7 Half size & 7 Full size racks (ST621/1021 FP).

Sets:

- 621 + ST621/1021 or ST621/1021 FP
- 1021 + ST621/1021 or ST621/1021 FP

HALF SIZE MODELS

There are several stands available for the installation of combi ovens 623, 611 and 1011 in a kitchen – standard with 16 racks (ST623, ST1116) or a stand with wheels for easy handling of the machine (ST 1116 CS, ST623 CS). There is a folding stand with eight racks available for models 611 and 1011.

Sets:

- 623 + ST623 or ST623 CS
- 611 + ST 1116 or ST 1116 CS or ST
- 1116 H or ST 1108 FP
- 1011 + ST 1116 or ST 1116 CS or ST
- 1116 H or ST 1108 FP



RETIGO VISION COMBI OVEN ON A CONSOLE

Even our smallest size of Retigo Vision 623 on a stand won't fit in your kitchen? Here's a solution for you. Mount the combi oven on your wall on a console. You will hardly find a bigger space saving.

Sets:

• 623 + wall-mount KN 623 console



ELECTRICAL RETIGO VISION COMBI OVEN SETS

Combi oven sets can increase your kitchen's capacity without taking up much more room. Various combi oven size combinations are available. Each set is automatically supplied with a stand under the set, brace for the bottom machine, bottom machine chimney connection set and a stainless steel collar for covering the gap between the machines.

Sets (bottom machine/top machine):

FULL SIZE MODELS

- 621i/621i + set kit
- 1021i / 621i + set kit

HALF SIZE MODELS

- 623i/623i + set kit
- 611i, b/611i, b + set kit
- 1011i, b/ 611i, b + set kit



GAS RETIGO VISION COMBI OVEN SETS

Also gas combi ovens may be installed in sets.

Available sets (bottom machine/top machine):

FULL SIZE MODELS

- 621ig/621ig + set kit
- 621ig/621i + set kit
- 621i/621ig + set kit
- 1021i/621ig + set kit
- 1021ig/621ig + set kit

HALF SIZE MODELS

- 611ig/611ig + set kit
- 611ig/611i, b + set kit
- 611i, b/611ig + set kit
- 1011i, b/611ig + set kit
- 1011ig/611ig + set kit



RETIGO VISION COMBI OVEN – REVERSE DOOR OPENING DIRECTION

As standard, Retigo Vision combiovens open from left to right (door hinges are on the right). Reverse door hinging is only available on half-size combi-ovens (623, 611 and 1011). The control panel remains on the left side of the combioven. The control panel remains on the left side of the combioven.



RETIGO VISION COMBI OVEN – CLEANING AGENTS

A necessary part of work with combi steamers and other equipment is their maintenance and cleaning. Retigo offers with its products an entire series of cleaning agents for automatic washing, washing by hand, decalcification of cooking chambers and boilers, grease removal and descaling. Cleaning and treating water is important not only for hygienic reasons, but proper maintenance also guarantees maximum service life of the equipment. More information at www.retigo.us.

Other accessories available at: www.retigo.us

Retigo's history commenced in 1994. The company has a narrow specialisation on the steam combi oven market segment. It focuses on high quality and affordability of its products. Retigo has Czech owners, and thus remains one of the last independent manufacturers of combi ovens in the world. Thanks to its financial stability and technological facilities, the company can flexibly react to the needs of its customers. One of the primary prerequisites for success is an outstanding level of sales and post-sales services.



PERFECTION IN COOKING

A professional approach, excellent food, satisfied customers, these are the bases of success. Retigo has been helping professionals in the food service industry for over 25 years.



PRECISE EQUIPMENT AT THE BEST PRICE

High quality and utility each and every day. The best prices among the TOP combi ovens on the market.



FOR EVERY TYPE OF OPERATION

A small restaurant, or company kitchen feeding hundreds? Retigo combi ovens will always meet your requirements. We specialise in combi ovens so we know how to help in the kitchen.



A SENSIBLE CHOICE

We advise our customers on how to select the optimal model and prevent over-investment into combi oven equipment that they will not fully utilise. Comprehensive support on the way to satisfied customers and rapid return on investment.



OUTSTANDING CUSTOMER SUPPORT

Problem-free cooking with a focus on the satisfaction of your diners.



COMBI OVEN SPECIALIST

RETIGO USA, Inc. 600 Eagleview Blvd. Suite 300, Exton PA 19341

E-mail: retigoUSA@retigo.us
Tel.: 610.883.9722
www.retigo.us

US-07/23